



PROTECH
TACTICAL

TECHNICAL SPECIFICATION

MODEL: DELTA X

TEST STANDARD	NIJ Standard 0106.01 Modified to address IIIA rounds/velocities
MODEL	DELTA X
THREAT TYPE	IIIA
NUMBER OF IMPACTS	4 Hits
TEST ROUND(S)	9mm 124 Gr. FMJ – 4 Impacts .44 Magnum 240 Gr. SJHP – 4 Impacts
STYLE	4 – Hole Bolt Pattern
SHELL DESIGNS	Standard Cut Mid – Cut High - Cut
SIZES	Small-Xlarge
Approximate Helmet Finished Shell Weight (Ballistic Composite and Paint) One Size Fits All (Large Shell)	<u>Standard Cut</u> ➤ 1.47 lbs (0.67 kg) <u>Mid-Cut</u> ➤ 1.37 lbs (0.62 kg) <u>High-Cut</u> ➤ 1.26 lbs (0.57 kg)
BALLISTIC MATERIAL	Aramid/Polyethylene
OUTER SHELL FINISHING	Non-Reflective Polyurethane Paint Standard Colors Available in Black, OD Green, & Tan <i>Textured</i>
SUSPENSION SYSTEM OPTIONS	<ul style="list-style-type: none">• Mesh Crown• Padding System• EPIC Air™ [Helmet Liner System]
SIZING (SUSPENSION SYSTEM)	Mesh Crown - Small, Medium, Large, Xlarge Padding System - One Size Fits All EPIC Air™ [Helmet Liner System] - One Size Fits All
Approximate Suspension WEIGHT	Mesh Crown ➤ 0.356 lbs (0.161 kg) Padding System ➤ 0.44 lbs (0.19 kg) EPIC Air™ [Helmet Liner System] ➤ 0.27 lbs (0.12 kg)
RETENTION SYSTEM OPTIONS	R2S Ratchet System CAM Fit™ System
SIZING (RETENTION SYSTEM)	R2S Ratchet System -One Size Fits All CAM Fit™ System - Medium/Large and XLarge <i>*Medium/Large Fits Most ACH and Some XL Wearers</i>
Approximate Retention WEIGHT	R2S Ratchet System ➤ 0.11 lbs (0.04 kg) CAM Fit™ System ➤ 0.25 lbs (0.11 kg)



Additional Accessories (Weight)	Shroud
	➤ 0.14 lbs (0.06 kg)
	Rails
	➤ 0.30 lbs (0.13 kg)