




PRODUCT FACT SHEET

TLR-1 Rail Mounted Tactical Light

MARKET APPLICATIONS:	Law Enforcement, Security, Military, Home Defense
DESCRIPTION:	Lightweight, compact design, lithium battery powered Gun-Mounted Tactical Light. Light is built with a Luxeon® Super Hi Flux LED providing at least 2.5 hours of continuous run time. Rail clamp designed to rapidly attach/detach from side of weapon.
CASE MATERIAL:	6000 Series machined aircraft aluminum with black anodized finish.
DIMENSIONS:	Length: 3.26 in. (8.28 cm) Width: 1.47 in. (3.73 cm) Height: 1.44 in. (3.65 cm)
WEIGHT:	4.18 oz (118.6 grams)*
LENS:	High temperature, shock mounted, impact resistant, Boro Float Glass lens.
LIGHT SOURCE:	3 Watt Luxeon® LED, impervious to shock with a 20,000 hour lifetime.
LIGHT OUTPUT:	LED Rating: 80 Lumens typical. Deep-dish parabolic reflector produces long-range targeting beam with optimum peripheral illumination to aid navigation.
ON/OFF:	Ambidextrous momentary/steady On-Off switch
RUN TIME:	2.5 hours continuous run time. Solid-state current regulation for consistent illumination level.
BATTERY:	Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.
FEATURES:	Super Hi Flux LED, ambidextrous momentary/steady On-Off switch. One handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Extensively live-fire tested impact resistant construction. Operating temperature: -40°F to +120°F. Waterproof to one meter.
APPROVALS**:	Meets applicable European Community Directives. 
WARRANTY:	"No Excuses" limited lifetime warranty.
OPTIONAL ACCESSORIES:	Mounting Adapters, Filters, Keys for S&W 99 and TSW

*With batteries (included in purchase).

Designed and Assembled in the U.S.A.