



TLR-2
Rail Mounted Tactical Light with Laser Sight

- MARKET APPLICATIONS:** Law Enforcement, Security, Military, Home Defense
- DESCRIPTION:** Lightweight, compact design, lithium battery powered Gun-Mounted Tactical Light with integrated aiming laser. Light is built with a shock-proof Luxeon® Super High Flux LED providing at least 2.5 hours of continuous run time when in dual mode with the high power visible laser. Rail clamp designed to rapidly attach/detach from side of weapon. Fits existing holsters.
- CASE MATERIAL:** 6000 Series machined aircraft aluminum with black anodized finish main body. High impact, chemically resistant engineering polymer laser housing.
- DIMENSIONS:** Length: 3.26 in. (8.28 cm) Width: 1.47 in. (3.73 cm) Height: 1.83in. (4.64 cm)
- WEIGHT:** 4.72 oz (133.8 grams)*
- LENS:** High temperature, shock mounted, impact resistant, Boro Float Glass lens.
- LIGHT SOURCE:** 3 Watt Luxeon® LED, impervious to shock with a 20,000 hour lifetime. 650-660 nm Laser
- LIGHT OUTPUT:** LED Rating: 80 Lumens typical. Deep-dish parabolic reflector produces long-range targeting beam with optimum peripheral illumination to aid navigation.
- ON/OFF:** Ambidextrous momentary/steady On-Off switch. Three position Mode Selector switch (Laser only, LED Illumination only, both)
- RUN TIME:** 2.5 hours continuous runtime, Laser/LED Simultaneously. Solid-state current regulation for consistent illumination level. 45+ Hours Laser-only mode.
- BATTERY:** Two (2) 3 Volt CR123A lithium battery, with a storage life of 10 years.
- FEATURES:** Super Hi Flux LED, ambidextrous momentary/steady On-Off switch. One handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Extensively live-fire tested impact resistant construction. Windage and Elevation adjustment screws mounted in brass bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. Operating temperature: -40°F to +120°F.
- APPROVALS**:** Meets applicable European Community Directives. **CE**
- WARRANTY:** "No Excuses" limited lifetime warranty.
- OPTIONAL ACCESSORIES:** Mounting Adapters, Filters, Keys for S&W 99 and TSW

*With batteries (included in purchase).